



MANUAL

Installation requirements

Aqara Curtain Driver E1

Track Version + Rod Version

Versie: 1.0

Datum: 15-08-2022



Installation requirements

Note: The curtain driver of the rod version can also be used on U-rails and I-rails, and the installation requirements are the same as those for the track version.

Track Version:

Video: https://youtu.be/aiMIJhkv8_0

U-rail, requirements: Bottom slot width ≤ 8 mm, and the bottom surface should be kept flat with no protrusions.

I-rail, requirements: Bottom width ≥ 10 mm, and the bottom surface should be kept flat with no protrusions and the circular arc bottom surface is not supported.

Caution: There must be no protrusions or steps on the rail caused by installing connecting devices.

Extendable rails are not supported

Vereisten of U-Rail & I-Rail Gliders:

- Runner distance between rail + hook opening = 16 - 25mm
- U-Rail runners without wheels are not supported

Rod Version:

Video: <https://youtu.be/VTmSyHQ21T8>

The curtain driver of the rod version supports rods with a diameter of 25–32 mm and a smooth surface, and extendable telescopic rods are not supported.

Types of curtains: Compatible with grommet curtains and ring top curtains.

Minimum Space Between Grommets: > 95 mm

Minimum Ring Thickness Curtain > 4 mm

Extendable rods are not supported